

Konabob (AH6GT) here:

When I am participating in the nets here in Hawaii, I am able to patch the audio from the Jitsi NETCAM chat room into my radio. If you would like to join the net using the patch, here are the printable instructions:

- 1) Open a computer window to <http://40meter.net> and click on the [<< Links] button just above to the left end of the yellow QRZ Box.
- 2) Next, select one of the SDRs on Maui or Oahu listed in the orange section at the bottom of the Links. Select the current NET FREQUENCY (Usually 7088). The SDR may take up to 20 seconds to come up online. Do not proceed until you can hear the SDR.
- 3) Click the [NETCAM] button in the red bar in the center of 40meter.net. Enter your Callsign and allow your browser to access your camera and microphone as you enter the NETCAM chat room.

If I am not in the room use the Dropdown menu in the yellow QRZ Box to get my attention.

You will listen to the net using the SDR, and keep an eye on the Web Roster which is on the right side of 40meter.net.

When I am taking my turn, make sure you can see me on the NETCAM, and that your NETCAM microphone is turned ON. Be ready to mute the SDR when you start talking, or it may distract you.

When I point to you on the NETCAM, you are on the air. Start by saying:

“This is [your callsign] using the AH6GT Patch”. Enjoy taking your turn.

Finish by turning the net back to me.